

GEARENCH™

PETOL™ FLANGE SPRAY DEFLECTOR

(Patent #9,200,734)

- ◆ *Minimizes spray when breaking flange sets*
- ◆ *Directs spray in a known direction*
- ◆ *Helps protect from chemical exposure and burns*

The PETOL™ FLANGE SPRAY DEFLECTOR minimizes the spray produced when a flange set is broken open and allows the operator to direct the spray into a known direction. This device is designed to help protect the worker from the dangers of chemical exposure, hot water and/or steam burns caused by the spray of pressurized liquid or gas when unbolting flanged connections. Suitable applications for this tool include first line breaks, low point breaks, hot bolting, blinding, and draining deflection and/or guiding. The PETOL Flange Spray Deflector's simple design consists of a nitrile elastomer strap, tension adjustment bolt and a tension clamp. **The flange spray deflector is not intended to seal or contain any pressure or replace personal protective equipment (PPE).**



CATALOG NO.	STRAP WIDTH	FITS FLANGE O.D. UP TO	WEIGHT
FD1	2"	22"	2 lbs.
FD2	2"	45"	2-3/4 lbs.



P.O. Box 192 • 4450 South Highway 6
Clifton, Texas 76634 U.S.A. • www.gearench.com
(254)675-8651 • fax (254)675-6100
sales@gearench.com

