

GEARENCH®

a division of Orbix Corporation

P.O. Box 192 • 4450 S. Hwy. 6
Clifton, Texas 76634
(254)675-8651 • fax (254)675-6100
sales@gearench.com

ISO9001
Quality
System
Certified

PETOL TANK SAFETY GAUGE INSTALLATION EQUIPMENT CHECKLIST

1. OSHA approved Breathing Apparatus and H₂S Monitor
2. Air Drill, Hoses and 23/64" Pilot Drill Bit
3. Nitrogen preferred for air drill power source – 60 lbs. pressure
4. Ladder, Measuring Tape and Pencil
5. Oil and container to pour oil into putty ring while drilling hole
6. Medium Sandpaper
7. Chalk Line with Plumb Bob
8. Plumber's Putty
9. Fiberglass Cloth (Roofing Type) cut in 3-1/2" x 5" pieces. (2 for each strap bracket)
10. Fiberglass resin and catalyst suitable for installation climate
11. 2 part Epoxy Glue
12. Small paint brush to apply resin
13. Matching paint to cover strap brackets and fiberglass on tank
14. Brass hammer and wooden dowel for installing nylon plug into hole in top of tank
15. Crimping tool for attaching sleeves to cable after stringing float and indicator
16. Copper hook used to “grab” cable and pull through hatch when attaching cable to float
17. Caulking gun with 100% silicone cartridge for securing A-Frame and/or Closed Hut
18. Gauge line for measuring fluid level in tank in order to set indicator at proper calibration
19. Masking Tape to secure cable on indicator temporarily until calibration is completed and sleeves are crimped in place
20. Nut Driver or Screw Driver for clamps. Wrenches for 7/16" Hex Nuts on bolted tank installations

SHOULD YOU HAVE ANY QUESTIONS AND/OR COMMENTS, PLEASE FEEL FREE TO
CONTACT US AT GEARENCH (254)675-8651 OR FAX (254)675-6100

